



Product Technical Description



Range:	Titan
Colour:	Avorio Matt
Group:	Bla (Fully vitrified porcelain)
Glazed:	Unglazed: X

Dimensions:			
Nominal Size:	600 x 600 mm.	Production Size:	av. 600.12mm Pass

Coefficient of Water Absorption: ($\leq 0.1\%$)	Test Results:	0.06%
--	---------------	-------

Abrasion Resistance:	PEI	V
-----------------------------	-----	---

Resistance to Chemical Attack:			
Acids & Alkalis:			
Low concentrations	ULA	Household Chemicals	UA
High concentrations	UHA		

Resistance to Scratching:	Max 22mm ³
----------------------------------	-----------------------

Stain Resistance:	Not affected
--------------------------	--------------

Slip Resistance:			
DIN Ramp Shod Foot Test:	R10	DIN Ramp Barefoot Test:	
Pendulum Test:	Dry: 59, Wet: 31		

- Recommendations:**
- Don't use cleaning agents that contain hydrofluoric acid.
 - We recommend installing floor tiles with a minimum grout joint of 1.5mm. Never install wall tiles without leaving a space of the minimum recommended grout joint.
 - For large format materials, we recommend fixing them with mortar which contains polymer additives and using the double fixing technique.
 - In the case of any doubt about the installation of wall tiles we recommend consulting the manufacturer.